
| 技術規格 Product Specification | |
|---------------------------------|--------------------------------|
| 型號 Model | TOC SERIES |
| 電壓 Voltage/頻率 Frequency | 220-240 V~ 50 Hz |
| 功率 Power | 200 W |
| 摩打轉速範圍 Motor Speed Range | 1,894-2,022 RPM |
| 排風量 Exhaust Flow | 300 m³/h |
| 風速選擇 Speed Selection | 3檔 Levels |
| 機身尺寸 Product Dimensions (HxWxD) | 102 x 600/700/800/900 x 485 mm |
| 淨重 Net Weight | 6.6-8.3 kg |
| 總重連包裝 Gross Weight w/Packing | 7.6-9.3 kg |
| 1 000 | |



*本產品排風量可能因應環境、溫度、氣壓、使用量等因素而出現誤差。 Exhaust flow of this product may vary due to factors such as environmental conditions, temperature, air pressure, and usage

抽油煙機系列 Range Hood Series



DCR-SC 智能同步變頻數碼

摩打抽油煙機 Smart Connect Super Inverter DC Motor Range Hood

XRZ 龍捲風台式 Tornado Wall-Mount Tyne



TFT 超薄抽拉式 Illtra Slim Slide-Out Tyne

產品規格及設計如有變更,恕不另行通知。最新版本以www.germanpool.com網上版為準。 中英文版本如有出入,一概以中文版為準。

All information in this pamphlet is for reference only. Specification and design are subject to change without prior notice. If there is any inconsistency or ambiguity between the English version and the Chinese version, the Chinese version shall prevail. Refer to www.germanpool.com for the most updated version.

德國寶(香港)有限公司

GERMAN POOL (HONG KONG) LIMITED

香港 Hong Kong

銅鑼灣 FASHION WALK 京士頓街9號 👲 +852 6530 5963 Fashion Walk, 9 Kingston Street, Causeway Bay T. +852 3110 2030

+852 9018 8648

佛山市順德區大良街道五沙新翔路8號 T. +86 757 2219 6888 8 Xinxiang Road, Wusha, Daliang, Shunde District, Foshan City

澳門青洲大馬路(青洲新路)515號 1 Andar A, Edf. Mei Kui Kuong Cheong Fase 2, 515 Av. do Conselheiro Borja

T. +853 2875 2699

九龍灣MegaBox L5-5舗 Shop L5-5, MegaBox, Kowloon Bay 更多產品資訊





















© 版權所有。未獲本公司授權,不得翻印、複製或使用本單張作任何商業用途。 © All rights reserved. Copying, reproducing or using the contents of this leaflet is not allowed. TOC-PS-24(1)



台式抽油煙機

TOC SERIES 外排風 循環過濾





有氣窗廚房 Kitchen With flue

外排煙模式下,簡單接駁排風管即可將油煙直接排出室外; 適合用於一般有氣窗的廚房。

Simply attach exhaust pipe to the outdoor to directly expel fumes;

Connect the exhaust pipe from the top of the range hood to the kitchen window,

and directly expel the greasy fumes outdoors.

MANAGEMENT OF THE PROPERTY OF

無氣窗廚房 Kitchen Without flue

循環過濾模式下,無需安裝排煙管,吸走的油煙經不銹鋼鎖油濾網及活性碳濾網雙重過濾後,於機身前方排出清新潔淨的空氣。
No need to install exhaust pipe; fumes sucked in by the range hood pass through the stainless steel grease-lock filter and double carbon filters, then recirculate out as clean air.





雙重過濾鎖住油煙 Double Filters Lock In Greasy Fumes

透過5層不銹鋼鎖油濾網及雙層活性碳濾網鎖住及過濾油煙,助您保持廚房清新舒適,爆炒過後頭髮、衣服仍然不沾油煙味。 Equipped with a 5-layer stainless steel grease-lock filter and double activated carbon filters, greasy fumes are locked and filtered clean, keeping your kitchen air, hair and clothes smelling fresh and clean even after cooking. 收起玻璃:適合慢燉 Retract glass for stewing

拉出玻璃:適合爆炒 Extend glass for stir-frying





可調式導煙玻璃 Adjustable FumeGuide Glass

抽油煙機前方的導煙玻璃可根據烹調情況自由調節導煙角度, 爆炒時拉出玻璃,將油煙導入吸風口;燜燉時將玻璃 向內收以縮小範圍,集中吸取蒸氣,大幅提高抽油煙效率。 Adjustable FumeGuide glass panel helps block greasy fumes from escaping, guiding the fume into the range hood; extend the glass panel to trap in greasy fumes, retract the glass to guide in steam.